


ABA Original



The trouble-free clamp with high tightening force and high breaking torque! Original clamps feature an extra strong one-piece pressed housing, rolled-up band edges and a smooth band underside that protects the hose.

- **W1 or S10:** Aluzink or galvanised band with electro zinc plated screw in blue housing.
- **W4 or S20:** All parts made of AISI 304 stainless steel.
- **W5 or S50:** All parts made of AISI 316 stainless steel.

Bandwidth: 12mm

Ø min - max (mm)	Max torque (Nm)	Box qty (pc)	Ref W1	Ref W4	Ref W5
8 x 14	4-5	50	C-ABA015	C-ABA015I	C-ABA015I316
11 x 17	4-5	50	C-ABA017	C-ABA017I	C-ABA017I316
13 x 20	4-5	50	C-ABA022	C-ABA022I	C-ABA022I316
15 x 24	4-5	50	C-ABA025	C-ABA025I	C-ABA025I316
19 x 28	4-5	50	C-ABA028	C-ABA028I	C-ABA028I316
22 x 32	4-5	50	C-ABA032	C-ABA032I	C-ABA032I316
26 x 28	4-5	50	C-ABA040	C-ABA040I	C-ABA040I316
32 x 44	5-6	50	C-ABA045	C-ABA045I	C-ABA045I316
38 x 50	5-6	50	C-ABA050	C-ABA050I	C-ABA050I316
44 x 56	5-6	50	C-ABA056	C-ABA056I	C-ABA056I316
50 x 65	5-6	50	C-ABA065	C-ABA065I	C-ABA065I316
58 x 75	5-6	50	C-ABA075	C-ABA075I	C-ABA075I316
68 x 85	5-6	50	C-ABA085	C-ABA085I	C-ABA085I316
77 x 95	5-6	50	C-ABA095	C-ABA095I	C-ABA095I316
87 x 112	5-6	50	C-ABA112	C-ABA112I	C-ABA112I316
104 x 138	5-6	50	C-ABA140	C-ABA140I	C-ABA140I316
130 x 165	5-6	50	C-ABA165	C-ABA165I	C-ABA165I316
150 x 180	5-6	50	C-ABA180	C-ABA180I	C-ABA180I316
175 x 205	5-6	50	C-ABA205	C-ABA205I	C-ABA205I316
200 x 231	5-6	50	C-ABA231	C-ABA231I	-
226 x 256	5-6	50	C-ABA260	C-ABA260I	-
251 x 282	5-6	50	C-ABA282	C-ABA282I	-
277 x 307	5-6	50	C-ABA310	C-ABA310I	-
298 x 328	5-6	50	C-ABA328	-	-
310 x 340	5-6	50	C-ABA340	-	-
345 x 375	5-6	50	C-ABA375	-	-
385 x 415	5-6	50	C-ABA415	-	-
435 x 465	5-6	50	C-ABA465	-	-
480 x 510	5-6	50	C-ABA510	-	-
502 x 532	5-6	50	C-ABA532	-	-
535 x 565	5-6	50	C-ABA565	-	-