

2002-001



VERSIONS COMPACTES : FILCORD C

| FILCORD 203 C | FILCORD 251 C | FILCORD 253 C | FILCORD 303 C | FILCORD 353 C |
|-------------------------|--------------------|--------------------|-------------------------|----------------------|
| 230 / 400 V - triphasée | 230 V - monophasée | | 230 / 400 V - triphasée | |
| 50 Hz | | | | |
| 19 - 11 A | 54 A | 27 - 16 A | 33 - 19 A | 41.5 - 24 A |
| 18 - 35 V | 20 - 53 V | 18 - 40 V | 18 - 45 V | 18 - 45 V |
| 27 - 200 A | 32 - 250 A | 35 - 250 A | 35 - 300 A | 35 - 350 A |
| 200 A (30 %) | 250 A (30 %) | 250 A (30 %) | 300 A | 350 A |
| 140 A | 180 A | 170 A | 230 A | 270 A |
| 110 A | 140 A | 140 A | 180 A | 210 A |
| 0,6-1,0 mm | 0,8-1,0 mm | 0,8-1,0 mm | 0,8-1,2 mm | 0,8-1,2 mm |
| 0,8-1,0 mm | 0,8-1,0 mm | 0,8-1,0 mm | 0,8-1,2 mm | 0,8-1,2 mm |
| 1,0 mm | 1,0 mm | 1,0 mm | 1,0-1,2 mm | 1,0-1,2 mm |
| 0,8-1,0 mm | 0,8-1,0 mm | 0,8-1,0 mm | 1,0-1,2 mm | 1,0-1,2 mm |
| IP 23 | | | | |
| EN 60974-1; -10 | | | | |
| H | | | | |
| 500 x 870 x 950 mm | 500 x 870 x 950 mm | 500 x 870 x 950 mm | 620 x 940 x 1,000 mm | 620 x 940 x 1,000 mm |
| 71 kg | 86 kg | 80 kg | 96 kg | 116 kg |
| 4 galets | | | | |
| Option W 000 352 093 | | | Oui | |
| 1 | 2 | | 2 | 3 |
| Oui | | | | |
| W 000 263 765 | W 000 263 764 | W 000 263 766 | W 000 263 767 | W 000 263 768 |
| W 000 267 147 | - | W 000 267 148 | W 000 267 149 | W 000 267 150 |
| WMT 25 A | | | WMT 36 A | |
| W 000 010 602 | | | W 000 010 605 | |
| W 000 010 603 | | | W 000 010 606 | |